

BathSelect Stainless Steel 14 Bar Wall Mount Towel Warmer In Gold Finish



BEFORE YOU BEGIN

Before you begin, please read the installation instructions below. Observe all local building and safety codes.

Unpack and inspect the items for any shipping damages. If you find damages, do not install.

Please note all products must be installed by a professional and certified plumber otherwise warranty might be voided.

POSSIBLE TOOLS REQUIRED*



Plumbers Tape



Tape Measure



Level



Adjustable Wrench



Hex Wrench



Thread Sealant



Drill



Pencil or Marker



Screwdriver

*not included

FITTING PROCEDURE (Wall mounted):

1. Remove radiator and fixing kit from box.
2. Remove the brass wall fixing pegs from the radiator. (These are inside the flanges)
3. Mark out the hole positions for the brass fixing pegs on the wall.
4. Drill holes and fix the pegs into position, using the screws and rawl plugs provided.
5. Push the radiator over the brass pegs, and secure the radiator using the grub screws located underneath the rail.
6. Hudson Reed radiator valves (not supplied) need to have a substantial length of PTFE tape wrapped around the thread, and then be screwed into the radiator inlets. (This is to create an adequate water seal.)
7. The copper inlet pipes are fed into the valves through the wall,(or floor) and are secured to the valves by tightening the nut up (The copper olive will make a watertight seal.)
8. Check for leaks.